ASSOCIATION CONNECTING LECTRONICS INDUSTRIES INDUSTRIES	nockburn, Illinois. A	ll rights reserved un ntions.	der both This docun level parts,	nent is a declara the declaration	tion of the substat encompasses all l	nces within the manufactur ower level materials for w	rer listed iter which the man	m. Note: if th nufacturer ha	e item is an ass s engineering i	embly with lower esponsibility.	
	IPC Web Site for Information on IPC-1752 Standard Form http://www.ipc.org/IPC-175x Distril			* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Information							
Supplier Information											
Company name* Company unique ID			Unique ID		e ID Authority			Response Date*			
isemi								2023-06-08			
Contact Name	zt Name Title - Contact			Phone - Contact*				Email - Contact*			
roduct-Env-Stewards Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
uthorized Representative* Title - Representative				Phone - Representative*				Email - Representative*			
Product-Env-Stewards Product Enviro Complia				NA	VA			Product-Env-Stewards@onsemi.com			
Requester Item Number Mf	r Item Number	Mfr Item Name		Effective Dat	e Version	Manufacturing Site		eight*	UOM	Unit Type	
NC	CP81101MNTWG Single-Phase Contr		roller with SVID Interface	2023-06-08		MY1	45	.91	mg	Each	
Manufacturing Proccess Information					-	·					
Terminal Plating / Grid Array Material	ninal Plating / Grid Array Material Terminal Base Alloy J		STD-020 MSL Rating	Peak Pro	cess Body Tempe	rature Max Time at Peak	Temperatur	re Number	of Reflow Cyc	les	
Matte Tin (Sn) - annealed CU Alloy 1			260	С	30	seconds	3 3				
Comments											
level 1 - maximum time at peak temperature duri	ng soldering is 10-3	0 seconds									
For more information regarding material compos	sition please refer to	page 3									

RoHS Material Composition Declaration				Declaration Type *	Detailed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU	RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).								
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe y others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of				
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted				
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all				
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the				
Supplier Digital Signature Ra	stislav Drska	Le							

## Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	3.28	mg	Supplier	Silicon (Si)	7440-21-3		3.28	mg
Die Attach	0.6	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.12	mg
			Supplier	Silver (Ag)	7440-22-4		0.48	mg
Lead Frame	17.25	mg	Supplier	Silver (Ag)	7440-22-4		0.345	mg
			Supplier	Iron (Fe)	7439-89-6		0.3795	mg
			Supplier	Copper (Cu)	7440-50-8		16.5255	mg
Mold Compound-Black	22.31	mg		Epoxy Phenol Resin	proprietary data		2.3425	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		19.9674	mg
Plating	2.2	mg	Supplier	Tin (Sn)	7440-31-5		2.2	mg
Wire Bond - Cu	0.27	mg	Supplier	Copper (Cu)	7440-50-8		0.27	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 signa range of distribution unless otherwise noted)