Product-Env-Stewards Product Enviro Compliance NA Product-Env-Stewards@onsemi.com Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Unit	ASSOCIATION CONNECTINE	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			der both	This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
Company name* Company name* Company name* Company name* Contact Name Contact Name Title - Contact Title - Contact Product Enviro Compliance NA Product-Env-Stewards Authorized Representative* Title - Representative Title - Representative Product Enviro Compliance NA Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards Product-Env-Stewards NA Product-Env-Stewards Onsemi.com Product-Env-Stewards Onsemi.com Manufacturing Site Weight* UOM Uni Manufacturing Site Weight* UOM Uni Manufacturing Process Information Manufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy I-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matter Tin (Sn) - annealed Comments	752-21.1											ials and Mf	g Informati	on	
Semilar Free	upplier Inform	nation													
Title - Contact Phone - Contact Phone - Contact Product-Env-Stewards Product-Env-	Company name* Company unique ID				ique ID		Unique ID Authority				Response Date*				
Product Envise Compliance NA Product Envise Compliance NA Product Envise © onsemi.com uthorized Representative* Title - Representative Phone - Representative* Product Envise Compliance NA Product Envise Compliance NA Product Envise © onsemi.com NA Nanufacturing Site Weight* UOM United Nanufacturing Process Information Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM United Naturing Process Information NCP303LSN16T1G ANA UNDERVOLT DETECT 1.6V 2023-06-08 MY1 14.08 mg Each Naturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matter Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3 Seconds Second	nsemi											2023-06-	08		
Authorized Representative* Product-Env-Stewards Product Enviro Compliance Requester Item Number Requester Item	ontact Name			Title - Contact			I	Phone - Contact*				Email - Contact*			
Product Enviro Compliance Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Uni NCP303LSN16T1G ANA UNDERVOLT DETECT 1.6V 2023-06-08 MY1 14.08 mg Eac Manufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy Terminal Plating / Grid Array Mater	Product-Env-Stewa	ards		Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com			
Requester Item Number	Authorized Representative* Tit				Title - Representative			Phone - Representative*			Email - Representative*				
NCP303LSN16T1G ANA UNDERVOLT DETECT 1.6V 2023-06-08 MY1 14.08 mg Eac	Product-Env-Stewa	ards	Product Enviro Compliance				NA				Product-Env-Stewards@onsemi.com				
Anufacturing Process Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Requeste	Requester Item Number Mfr		r Item Number Mfr Item Name			ı		Version	Version Manufacturing Site		V	Veight*	UOM	Unit Type
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycles Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3			NCP303L	SN16T1G	ANA UNDERVOL	T DETECT 1.0	6V	2023-06-08		N	MY1	1	4.08	mg	Each
Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3 comments				arminal Paga	Alloy	STD 020 MSI	Pating	Dook Proc	ages Pody (Comporative	May Time at Pack	Tomporati	uro Numb	or of Poflow Cur	alas
omments					Alloy J-1	31D-020 MSL	Kating		ess body	T *				er of Reflow Cyc	iles
	•	n (Sn) - anneaieu		U Alloy	1			200		IC	30	second	18 3		
ver 1 - maximum time at peak temperature during soldering is 10-50 seconds		ima at maak tammar-t	duning s-1-	doning is 10. 1	10 seconds										
or more information regarding material composition please refer to page 3															

RoHS Material Composition Declaration			Declaration Type *	Detail	ed				
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		ium (Cr6+), Polybrominated Biphenyls (PB)	erial for Cadmium and quantity limit of 0.1% b B), Polybrominated Diphenyl Ethers (PBDE), a						
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct at it in member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of				
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted				
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.									
Exemption List Version	EL-2011/534/EU								
Declaration Signature									
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the				

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.42	mg	Supplier	Silicon (Si)	7440-21-3		0.42	mg
Die Attach	0.11	mg	Supplier	Silver (Ag)	7440-22-4		0.088	mg
			Supplier	Phenolic Resin-2	54208-63-8		0.022	mg
Lead Frame	5.78	mg	Supplier	Silver (Ag)	7440-22-4		0.0705	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0069	mg
			Supplier	Iron (Fe)	7439-89-6		0.1358	mg
			Supplier	Copper (Cu)	7440-50-8		5.565	mg
			Supplier	Phosphorus (P)	7723-14-0		0.0017	mg
Mold Compound-Black	7.34	mg		Epoxy resin	proprietary data		0.367	mg
			Supplier	Phenolic Resin	Proprietary Data		0.367	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.1468	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0367	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		6.4225	mg
Plating	0.39	mg	Supplier	Tin (Sn)	7440-31-5		0.39	mg
Wire Bond - Au	0.04	mg	Supplier	Gold (Au)	7440-57-5		0.04	mg