© Cop	rial Composition yright 2005. IPC, Ba tional and Pan-Ame	annockbur	rn, Illinois. A	ll rights reserved utions.	under both	This docume level parts, t	ent is a decla he declaratio	aration con encor	of the subs mpasses a	stances w 11 lower l	thin the manuferent termination the manuferent termination of the material states of the manuferent termination of termination	acturer listed for which the	l item. I manuf	Note: if th acturer ha	e item is an ass s engineering r	embly with lower esponsibility.
	IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				e *	Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater					Iaterials and	als and Mfg Information				
Supplier Information																
Company name*			Company unique ID			Unique ID Authority					Respo	Response Date*				
onsemi											2023-0	2023-06-07				
Contact Name			Title - Contact]	Phone - Contact*					Email	Email - Contact*			
Product-Env-Stewards			Product Enviro Compliance				NA					Produ	Product-Env-Stewards@onsemi.com			
Authorized Representative*			Title - Representative			Phone - Representative*				Email	Email - Representative*					
Product-Env-Stewards			Product Enviro Compliance				NA					Produ	Product-Env-Stewards@onsemi.com			
Requester Item Nu	er Item Number Mfr Item		Number Mfr Item Name				Effective D	Date Version Manufacturing Site		te	Weig	nt*	UOM	Unit Type		
	N	NLX1G99DMUTWG		CONFIG MULTIFUNCTION GATE		GATE	2023-06-07	7		М	MY1		2.83		mg	Each
Manufacturing Proces	ss Information						·									
Terminal Plating /	Terminal Plating / Grid Array Material		erminal Base Alloy J-S		J-STD-020 MS	L Rating	Peak P	eak Process Body Temperatu		perature	ure Max Time at Peak Temp		mperature Number of Reflow		of Reflow Cycl	es
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		(no CU	U Alloy 1		1		260		C	2	30 sec		seconds 3			
Comments																
evel 1 - maximum time at pe	ak temperature du	ring solde	ering is 10-3	0 seconds												
For more information regard	ling material comp	osition pl	ease refer to	page 3												

RoHS Material Composition Declaration				Declaration Type *	Detailed
Directive 2015/863/EU amending RoHS Directive 2011/65/EU		nium (Cr6+), Polybro	ominated Biphenyls (PBB), Polybron	dmium and quantity limit of 0.1% by mass (100 minated Diphenyl Ethers (PBDE), and Bis(2-eth	
cadmium, hexavalentchromium, polybrominate contains a RoHS restricted substance inexcess encompass all such components. Supplier certif as of the date that Supplier completes this form Company acknowledges that Supplier may hav independently verified information provided by certification in this paragraph. If the Company a	ed biphenyls and/or polybrominated dip of an applicable quantity limit, please ir ies that it gathered the information it pro- .Supplier acknowledges that Company e relied on informationprovided by othe v others, Supplier agrees that, at a minin and the Supplier enter into a written agre pource of the Supplier's liability and the	henyl ethers (each a " ndicate below which, i ovides in this form us will rely on this certifiers in completing this num, itssuppliers have eement with respect to Company's remedies	RoHS restricted substance") in exce if any, RoHS exemption you believe ing appropriate methods to ensure if ication in determining the complian form, and that Supplier may not have e provided certifications regarding the to the identified part, the terms and cc for issues that arise regarding inform	ce of its products with European Union membe	ove. If a homogeneous material within the part er level components, the declaration shall l correct to the best of its knowledge and belief, r state laws that implement the RoHS Directive. wever, in situations where Supplier has not tions are at least as comprehensive as the anty rights and/or remedies provided as part of
RoHS Declaration * 1 - Item(s)	does not contain RoHS restricted substa	ances per the definitio	on above	Supplier Acceptance	* Accepted
Exemption: If the declared item does not con applicable exemptions.	ntain RoHS restricted substances per	the definition above	except for defined RoHS exempti	ons, then select the corresponding response i	n the RoHS Declaration above and choose all
Exemption List Version	EL-2011/534/EU				
Declaration Signature					
Instructions: Complete all of the required fin Requester) and click on Submit Form to have	elds on all pages of this form. Select the form returned to the Requester	he "Accepted" on th	e Supplier Acceptance drop-down	. This will display the signature area. Digital	lly sign the declaration (if required by the
Supplier Digital Signature Ra	stislav Drska	Le			

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.08	mg	Supplier	Silicon (Si)	7440-21-3	1	0.08	mg
Die Attach	0.12	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.0384	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.0816	mg
Lead Frame	0.69	mg	Supplier	Zinc (Zn)	7440-66-6		0.0007	mg
			Supplier	Iron (Fe)	7439-89-6		0.0152	mg
			Supplier	Copper (Cu)	7440-50-8		0.6741	mg
Mold Compound-Black	1.89	mg		Epoxy Phenol Resin	proprietary data		0.1701	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		1.7199	mg
Plating	0.01	mg	Supplier	Palladium (Pd)	7440-05-3		0.0003	mg
			В	Nickel (Ni)	7440-02-0		0.0096	mg
			Supplier	Gold (Au)	7440-57-5		0.0001	mg
Wire Bond - Au	0.04	mg	Supplier	Gold (Au)	7440-57-5		0.04	mg

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).