consemi Contact Name Title - Contact Product-Env-Stewards Product Enviro Compliance Authorized Representative* Title - Representative Phone - Contact* Email - Contact* Product-Env-Stewards@onsemi.com Product-Env-Stewards@onsemi.com Email - Representative*	©	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.			This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.									
Company name* Company unique ID Unique ID Authority Description Desc											formation			
Semilar Contact Name Title - Contact Phone - Contact* Phone - Contact* Product-Env-Stewards Product-Enviro Compliance NA Product-Env-Stewards@onsemi.com Phone - Representative* Phone - Representative* Phone - Representative* Product-Env-Stewards@onsemi.com Requester Item Number Mfr Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Product-Env-Stewards@onsemi.com Phone - Representative* Phone - Representative* Product-Env-Stewards@onsemi.com Requester Item Number Mfr Item Name Effective Date Version Manufacturing Site Weight* UOM Phone - Representative* Phone - Representative* Product-Env-Stewards@onsemi.com Phone - Representative* Product-Env-Stewards@onsemi.com Phone - Representative* Product-Env-Stewards@onsemi.com Product-Env-Steward	ier Informatio	ion												
Product-Env-Stewards Undorized Representative* Product-Env-Stewards Product Enviro Compliance Product-Env-Stewards	Company name*			Company unique ID			Unique ID Autho	ority	Response Da	Response Date*				
Product-Env-Stewards Authorized Representative* Product-Env-Stewards Product Enviro Compliance Product-Env-Stewards Product-Env-Steward								2023-06-08	2023-06-08					
Authorized Representative* Product-Env-Stewards Requester Item Number Mfr Item Number Mfr Item Number Mfr Item Name CS5173GDR8G ANA 1.5A BOOST REGULATOR Deak Process Information Terminal Plating / Grid Array Material Terminal Base Alloy Matte Tin (Sn) - annealed Title - Representative Phone - Representative* NA Product-Env-Stewards@onsemi.com Manufacturing Site Weight* UOM PH1 72.0 mg Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Number of Reflow Cycle Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Contact Name			Title - Contact			Phone - Contact*			Email - Con	Email - Contact*			
Product-Env-Stewards Requester Item Number Mfr Item Number Manufacturing Site Weight* UOM Manufacturing Proccess Information Manufacturing Site Weight* UOM Manufacturing Proccess Information Manufacturing Site Weight* Womber Mfr Item Number Manufacturing Site Weight* UOM Manufacturing Site Weight* UOM Manufacturing Proccess Information Manufacturing Site Weight* UOM Manufacturing Site Weight* UOM Manufacturing Proccess Information Manufacturing Site Weight* UOM	Product-Env-Stewards			Product Enviro Compliance			NA			Product-En	Product-Env-Stewards@onsemi.com			
Requester Item Number	Authorized Representative*			Title - Representative			Phone - Representative*			Email - Rep	Email - Representative*			
CS5173GDR8G ANA 1.5A BOOST REGULATOR 2023-06-08 PH1 72.0 mg Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Product-Env-Stewards			Product Enviro Compliance			NA			Product-En	Product-Env-Stewards@onsemi.com			
Manufacturing Proccess Information Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3	Requester Iter	tem Number	Mfr Item Num	ımber Mfr Item Name	Mfr Item Name		Effective Date	Version	Manufacturing Site	Weig	ght* UO	M	Unit Type	
Terminal Plating / Grid Array Material Terminal Base Alloy J-STD-020 MSL Rating Peak Process Body Temperature Max Time at Peak Temperature Number of Reflow Cycle Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3			CS5173GDR8	R8G ANA 1.5A BOO	OST REGULAT	OR	2023-06-08		PH1	72.0	mg	1	Each	
Matte Tin (Sn) - annealed CU Alloy 1 260 C 30 seconds 3				ainal Daga Alloy	L STD 020 MS	CI Pating	Dook Proces	ss Pody Tompo	watura May Timo at Pa	ak Tamparatura	Number of Pet	Flow Cycles		
	ž ž			•		SL Kanng					1	low Cycles		
OHIHERIS	•	511) - alillealeu	CU AI	Anoy	1		200	IC_	30	seconds	13			
		a at most tommonature d	luuina aaldanis	ring is 10, 20 seconds										
vel 1 - maximum time at peak temperature during soldering is 10-30 seconds or more information regarding material composition please refer to page 3		_ •												

RoHS Material Composition Declaration			Declaration Type *	Detail	ed					
Directive 2015/863/EU amending RoHS Directive 2011/65/EU RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).										
cadmium, hexavalentchromium, polybromin contains a RoHS restricted substance inexce encompass all such components. Supplier cet as of the date that Supplier completes this Company acknowledges that Supplier may hindependently verified information provided certification in this paragraph. If the Compan	nated biphenyls and/or polybrominated diphess of an applicable quantity limit, please indriffes that it gathered the information it provom. Supplier acknowledges that Company wave relied on informationprovided by others of the supplier agrees that, at a minimusy and the Supplier enter into a written agree yesource of the Supplier's liability and the C	enyl ethers (each a "RoHS restricted substan licate below which, if any, RoHS exemption vides in this form using appropriate methods vill rely on this certification in determining the s in completing this form, and that Supplier um, itssuppliers have provided certifications ement with respect to the identified part, the tompany's remedies for issues that arise rega	s of the European Union member states) of the ce") in excess of the applicable quantity limit is you believe may apply. If the part is an assemb to ensure its accuracy and that such informatio e compliance of its products with European Ur may not have independently verified such infor regarding their contributions to the part, and the erms and conditions of that agreement, including information the Supplier provides in this	dentified above. If a ally with lower level in is true and correct at it in member state la mation. However, in ose certifications are ag any warranty righ	homogeneous material within the part components, the declaration shall to the best of its knowledge and belief, was that implement the RoHS Directive. In situations where Supplier has not the at least as comprehensive as the lats and/or remedies provided as part of					
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substar	nces per the definition above	Supplier A	cceptance *	Accepted					
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.										
Exemption List Version	EL-2011/534/EU									
Declaration Signature										
		e "Accepted" on the Supplier Acceptance	drop-down. This will display the signature a	rea. Digitally sign t	the declaration (if required by the					

Homogeneous Material Composition Declaration for Electronic Products

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	1.33	mg	Supplier	Silicon (Si)	7440-21-3		1.33	mg
Die Attach	2.4	mg		Epoxy resin	proprietary data		0.24	mg
			Supplier	Ethylene dimethacrylate	97-90-5		0.12	mg
			Supplier	Silver (Ag)	7440-22-4		1.92	mg
			Supplier	Formaldehyde Polymer	9003-36-5		0.12	mg
Lead Frame	37.61	mg	Supplier	Silver (Ag)	7440-22-4		0.7898	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0752	mg
			Supplier	Iron (Fe)	7439-89-6		0.9403	mg
			Supplier	Copper (Cu)	7440-50-8		35.8047	mg
Mold Compound-Black	28.58	mg		Epoxy resin	proprietary data		1.429	mg
			Supplier	Phenolic Resin	Proprietary Data		0.5716	mg
			Supplier	Ortho Cresol Novolac Resin	29690-82-2		0.7145	mg
			Supplier	Carbon Black (C)	1333-86-4		0.1429	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		25.722	mg
Plating	1.89	mg	Supplier	Tin (Sn)	7440-31-5		1.89	mg
Wire Bond - Au	0.19	mg	Supplier	Gold (Au)	7440-57-5		0.19	mg